

1. ELECTRICAL SPECIFICATION

Uncertainty is indicated as \pm (% rdgs + no. of dgt) at 23°C \pm 5°C, con relative humidity <80%HR

DC/AC TRMS VOLTAGE

Range	Resolution	Uncertainty	Overload protection
10 ÷ 660V	1V	$\pm(2\%rdg+2dgt)$	CAT IV 600 to ground

INSULATION RESISTANCE

Range	Test Voltage	Resolution	Uncertainty (*)
0.01M Ω ÷ 0.19M Ω	$\geq 100V$ DC	$\leq 1\%rdg$	$\pm(5\%rdg + 7dgt)$
0.20M Ω ÷ 199G Ω			$\pm(5\%rdg.+3dgt)$ if $R_{mis} \leq \frac{Test\ Voltage}{5nA}$
0.20M Ω ÷ 499G Ω	$\pm(20\%rdg.+3dgt)$ if $R_{mis} > \frac{Test\ Voltage}{5nA}$		
0.20M Ω ÷ 999G Ω			$\geq 500V$ DC
0.20M Ω ÷ 1.99T Ω	$\geq 1000V$ DC		
0.20M Ω ÷ 4.99T Ω			$\geq 2500V$ DC
0.20M Ω ÷ 9.99T Ω	5000V DC		

(*) Load Capacitance < 1nF

GENERATED TEST VOLTAGE (compliance to IEC/EN61557-2)

Test mode	Nominal test voltage	Uncertainty
FIX	100V, 250V, 500V, 1kV, 2.5kV, 5kV	-0%, +10% +15V
AJUSTABLE	100 ÷ 1kV in steps of 25V	
	1kV ÷ 5kV in steps of 50V	
RAMP	100 ÷ 1kV in steps of 25V	
	1kV ÷ 5kV in steps of 50V	

TEST CURRENT

Test Voltage	Test current
100 ÷ 5000V	1mA \leq Test Current \leq 3mA (**)

(**) Test current automatically controlled.

TEST TIME

Setting Range	Resolution
5s – 99min 59s	1s

CAPACITANCE

Range	Resolution	Resistance Load	Test Voltage (Vn)	Uncertainty
1nF ÷ 999nF	1nF	$\geq 5M\Omega$	Vn \leq 5kV	$\pm(10\%rdg+5dgt)$
1.00 μ F ÷ 5.00 μ F	0.01 μ F			
1nF ÷ 999nF	1nF		Vn \leq 2.5kV	
1.00 μ F ÷ 9.99 μ F	0.01 μ F			
10.0 μ F ÷ 19.9 μ F	0.1 μ F		Vn \leq 1kV	
1nF ÷ 999nF	1nF			
1.00 μ F ÷ 9.99 μ F	0.01 μ F			
10.0 μ F ÷ 49.9 μ F	0.1 μ F			

Capacitor charge time (OV \rightarrow 5000V): < 3s x 1 μ F

Capacitor discharge time (5000V \rightarrow 25V): < 5s x 1 μ F

LEAKAGE CURRENT

Range	Resolution	Uncertainty
1nA ÷ 99.9nA	0.1nA	$\pm(7\%rdg+3dgt)$ if $R_{mis} \leq \frac{Test\ Voltage}{5nA}$
100nA ÷ 999nA	1nA	
1.00µA ÷ 9.99µA	0.01µA	$\pm(22\%rdg+3dgt)$ if $R_{mis} > \frac{Test\ Voltage}{5nA}$
10.0µA ÷ 9.99µA	0.1µA	
100µA ÷ 999µA	1µA	
1.00mA ÷ 2.5mA	0.01mA	

P.I (Polarization Index) – D.A.R (Dielectric Absorption Ratio)

Range	Resolution	Uncertainty
0.01 ÷ 9.99	0.01	$\pm(5\%rdg+3dgt)$ if $R_{mis} \leq \frac{Test\ Voltage}{5nA}$
		$\pm(20\%rdg+3dgt)$ if $R_{mis} > \frac{Test\ Voltage}{5nA}$


(*) Load Capacitance < 1nF

2. GENERAL CHARACTERISTICS

DISPLAY, MEMORY, SERIAL INTERFACE

- Backlight LCD with three simultaneous readings:
Group 1 (main) → Insulation Resistance, Leakage Current, PI, DAR, Capacitance
Group 2 → Test voltage (nominal and generated)
Group 3 → Test Time
- Bargraph: 32 segments
- Low battery indications
- Memory: 700 test
- Communication interface: RS232 optoinsulated

POWER SUPPLY:

- Internal battery charger, power supply: 220-240V 50/60Hz, 20VA
- Internal NiMH rechargeable battery
- Protection fuse on power supply: T 200mA/250V, Ir: 1.5kA
- Low battery indication:  symbol at display
- Battery life: >1000 Test @ 5kV on 5MΩ (test time: 5s, delay between two test: 25s)
according to IEC/EN61557-2. (par. 6.7)
- AutoPowerOFF: after 5min since last operation

ENVIRONMENT:

- Ref. Temperature: 23°C ± 5°C
- Working temperature: 0° ÷ 40°C
- Maximum relative humidity: < 80%UR
- Storage temperature: -10 ÷ 60°C
- Storage humidity: < 80%UR

MECHANICAL DATA:

- Dimensions: 360(L) x 310(W) x 195(H) mm
14.2" (L) x 12.2"(W) x 7.7"(H)
- Weight: about 3.5kg
about 7.8lv

GUIDELINES

Instrument's safety	IEC/EN61010-1, IEC/EN61557-1, IEC/EN61557-2
Technical documentation :	IEC/EN61187
Accessories safety :	IEC/EN61010-031
Insulation:	Double insulation
Type of Protection:	2
Mechanical protection:	IP40 (open case), IP53 (closed case)
Over voltage category:	CAT IV 600V to ground, max 600V between inputs
Maximum altitude	max altitude 2000m
Patented certification:	TÜV protocol conformity

This instrument complies with the requirements of the European Low Voltage Directives 2006/95/EEC (LVD) and EMC 2004/108/EEC