

Dew point set IDS 52 for refrigeration dryers

consisting of:

- Digital process meter IDS 52

- Standard measuring chamber



- Dew point sensor IFA 415

The measuring range of $-20...50^{\circ}\text{Ctd}$ makes the dew point set IDS 52 with alarm the ideal dew point monitor with analogue output $4...20\text{ mA}$.

The dew point sensor IFA 415 ist extremely long-term stable and can be installed and removed quickly and easily under pressure by means of the screwable measuring chamber including quick coupling. The dew point set is supplied ready for plug-in, i.e. everything is completely wired. The alarm values can be freely ad-justed.

Special features:

- System ready for plug-in: Everything completely wired
- No time-consuming studying of the instruction manual
- 2 alarm contacts (230 VAC, 3 A) pre- and main alarm freely adjustable
- $4...20\text{ mA}$ analogue output
- Option alarm unit: Buzzer and continuous red light

Technical data display IDS 52:

Dimensions:	118 x 92 x 93 mm
Display:	LED red, 7 segments, height: 13 mm, 5 digits, 2 LED for alarm relay
Keypad:	4 keys
Input:	dew point sensor FA 415
Power supply:	230 VAC, 50/60 Hz; Option: 24 VDC or 110 VAC 50/60 Hz
Alarm outputs:	2 x relay output, changeover contact, 250 VAC, max. 3 A
Operating temperature:	$-10...+60^{\circ}\text{C}$ (storage temp. $-20^{\circ}\text{C}...+80^{\circ}\text{C}$)
Alarm thresholds:	freely adjustable
Hysteresis:	2°Ctd
Analogue output:	$4...20\text{ mA} = -80...20^{\circ}\text{Ctd}$

Technical data dew point sensor IFA 415

Measuring range:	$-20...50^{\circ}\text{Ctd}$
Accuracy:	$\pm 1^{\circ}\text{C}$ at $0...20^{\circ}\text{Ctd}$ $\pm 2^{\circ}\text{C}$ remaining range
Pressure range:	$-1...16\text{ bar}$
Protection class:	IP 65
EMV:	according to DIN EN 61326
Operating temp:	$-20...70^{\circ}\text{C}$
Connection:	M12, 5 pole
PC connection:	SDI interface
Burden for analogue output:	$< 500\ \Omega$
Screw-in thread:	G 1/2" without meas. chamber

Description	Order No.
Dew point set IDS 52 for refrigeration dryers, consisting of:	0600 0425
IDS 52 LED digital process meter in wall housing	0500 0008
IFA 415 dew point sensor ($-20...50^{\circ}\text{Ctd}$)	0699 0415
Standard measuring chamber up to 16 bar	0699 3390
Connection cable for IVA/IFA Series, 5 m with M12 plug	0553 0104
Options:	
Power supply 24 VDC (instead of 230 VAC)	Z500 0001
Power supply 110 VAC (instead of 230 VAC)	Z500 0002
Alarm unit mounted at wall housing	Z500 0003
Alarm unit for external mounting with 5 m cable	Z500 0004
Additional accessory:	
Precision calibration at 3°Ctd including ISO certificate	3200 0003