

MAVO - SPOT 2 USB

Luminance Spotmeter with measuring angle of 1°,
Accuracy Class B

Features

- High precision spotmetering of the luminance with a measuring angle of 1° according to DIN 5032-7, Class B and DIN EN 13023-1, Appendix B
- SLR viewfinder with measuring circle of 1° and viewing field of 15°
- Measuring from the distance from 1 m to ∞, with close-up lenses (optional) down to 34 cm
- Contact measurement with optional Measuring Probe
- Backlight display illumination with LCD read-out in the viewfinder
- The silicon photo diode is colour corrected, i.e. its spectral responsivity is matched to the photopic daylight vision of the human eye $V(\lambda)$
- Remarkably easy, one hand use, with only four buttons and 1 sliding switch
- Configuration via DIP Switches in the battery compartment
- Automatic measuring range selection, total range 0.01 cd/m² to 99.990 cd/m² subdivided in four measuring ranges and 0,003 to 29.187 foot Lambert
- Data memory for up to 1000 single measuring values, or alternatively in 10 groups
- USB 2.0 Port
- Tripod socket
- CD Rom included with software for visualizing and processing the values measured and controlling the meter.
- Aluminum transport case, USB cable incl. in the supply



The high reliability and precision make the MAVO-SPOT 2 USB ideally suitable for measuring:

- Monitors taking into consideration the ambient light, e.g. official inspections or constancy tests in medical applications according to DIN 6868-57 and IEC 61223-2-5. For luminance measurement at viewing monitors in computer tomography, digital radiography, viewing panels for X-ray films and other medical systems.
- Lighting of streets, roads, tunnels and airfields
- Light reflections at work places according to the applicable Protective Laws and regulations for people at work
- Lighting in museums, in public buildings and places
- Projection screens, for checking the uniformity of the illumination

Specifications:

Type	Luminance meter, with precision single lens reflex optical system, display in view-finder
Measuring angle	1 °
Accuracy	Class B according to DIN 5032-7 in all chapters and DIN EN 13032-1, Appendix B
Optical system	Stray light error ambient light (fs (u) < 2%)
Field of view	15 ° diagonal
Focusing distance	1 m to ∞ - focusing with external ring at the lens
Light sensor	Silicon photo diode with V(λ) filter (f1 < 3%)
Luminance measuring unit	cd/m ² or fL (selectable with DIP switches)
Measuring ranges	Automatic measuring range selection 0.01 cd/m ² to 99 990 cd/m ² in four ranges or 0,003 fL to 29 187 fL in four ranges
Measuring functions	Luminance in cd/m ² or fL (selectable) Luminance percentage Memory MEM Correction Factor CORR Measuring the illuminance (Lux) with GOSSEN Reflexion Standard (optional accessory)
Measuring mode	Measurement from the distance (Close-up lenses for shorter distances, optional accessories) Contact measurement (Measuring Probe for contact measurement, optional accessory)
Data memory	Up to 1000 individual measurement values, or in 10 groups (adjustable with DIP switch in the battery compartment)
USB Port	USB 2.0 (1.1 compatible)
Operating elements	Easy to use with 4 buttons, 1 sliding switch Configuration with DIP switches in the battery compartment
Operating temperature	0° C to 50° C, According to EN 61010-1:2001, cl. 1.4.1
Storage temperature	-20°C to +70°C
Power supply	2 x 1,5 V, size AA, when connected to PC, power will be supplied via the USB cable
Software	gLux software and additional applications
Others	Tripod socket
Weight	appr. 400 g without batteries
Standard equipment	Meter in aluminum transport case, gLux software incl. meter driver, USB cable, lens cover, eye piece, batteries and instruction manual
Optional accessories	Close-up lens 1 (51 cm to 100 cm), close-up lens 2 (34 cm to 50 cm), Measuring Probe for contact measurement, Reflexion Standard for Lux measurement, Stray light screen, Carrying strap

MAVO-SPOT 2 *USB*



The MAVO-SPOT 2 *USB* is supplied in a practical, strong aluminum transport case



Measuring probe for contact measurements



GOSSEN Reflexion Standard



Close-up lenses 1 and 2



Carrying strap

Ordering information:

Description	Ordering code
Mavo-Spot 2 USB incl. Aluminum transport case, USB cable, CD Rom, lens cover, eye piece. batteries, instruction manual	M508G
Measuring probe for contact measurement, incl. adapter disk and lens cover	M511G
Close-up lens 1 (measurement between 51 cm and 100 cm)	M496G
Close-up lens 2 (measurement between 34 cm and 50 cm)	M497G
GOSSEN - Reflexion Standard for measuring Lux	M512G
Stray light screen	M513G
Carrying strap	M514G
Adapter ring for Gx - measurement	M498G
Calibration Certificate for MAVO-SPOT 2 (Please refer to page 12)	H997B