

Counting scale KERN CKE



Easy to use, self-explanatory counting scale with laboratory accuracy, counting resolution up to 360,000 points

Features

- Self-explanatory graphic control panel, the workings steps can be understood immediately, even without operating instructions
 - no learning time = reduces costs
 - ideal for untrained users
 - visualised process avoids operating errors
- The 4 steps are carried out from left to right:
 - 1 Place the empty container onto the weighing plate and tare by pressing the TARE key
 - 2 Place the reference quantity for the goods to be counted into the container (5, 10 or 20 pieces)
 - 3 Confirm the selected reference quantity by pressing the key (5, 10 or 20)
 - 4 Pour in the goods to be counted. The number of pieces will immediately be shown in the display
- Precise counting: The automatic reference weight optimisation of reference weight gradually improves the average piece weight value

- Two balances in one: Changes from counting mode to weighing mode at the touch of a key
- Draught shield standard for models with weighing plate size \varnothing 81 mm, weighing space \varnothing 90×40 mm
- Protective working cover included with delivery

Technical data


- Large backlit display
 - A, B digit height 9 mm
 - C digit height 18 mm
- Dimensions weighing surface
 - A \varnothing 81 mm, plastic
 - B W×D 150×170 mm, stainless steel
 - C W×D 340×240 mm, stainless steel
- Overall dimensions W×D×H
 - A, B 167×250×85 mm
 - C 350×390×120 mm

- Optional battery operation, 6×1.5 V Size C not included, operating time up to 40 h, for models with weighing plate size C
- Permissible ambient temperature 10 °C/40 °C


Accessories

- Protective working cover, scope of delivery: 5 items, for models with weighing plate size
 - A KERN PCB-A02S05
 - B KERN PCB-A05S05
 - C KERN FKB-A02S05
- Rechargeable battery pack external, operating time up to 30 h without backlight, charging time approx. 10 h, KERN KS-A01
- Internal rechargeable battery pack, operating time up to 30 h without backlight, charging time approx. 10 h, for models with weighing plate size A, B, KERN KB-A01N
- USB data interface, for transferring weighing to the PC, printer etc., for models with weighing plate size C, KERN CKE-A02
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION










































FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Smallest part weight [Normal] g/piece	Counting resolution Points	Net weight approx. kg	Weighing plate	Option	
							DAkKS Calibr. Certificate	
KERN							DAkKS KERN	
CKE 360-3	0,36	0,001	0,01	360.000	1	A	963-127	
CKE 2000-2	2	0,01	0,1	200.000	1,8	B	963-127	
CKE 3600-2	3,6	0,01	0,1	360.000	1,8	B	963-127	
CKE 6K0.02	6	0,02	0,2	300.000	7	C	963-128	
CKE 8K0.05	8	0,05	0,5	160.000	7	C	963-128	
CKE 16K0.05	16	0,05	0,5	320.000	7	C	963-128	
CKE 16K0.1	16	0,1	1	160.000	7	C	963-128	
CKE 36K0.1	36	0,1	1	360.000	7	C	963-128	
CKE 65K0.2	65	0,2	2	325.000	7	C	963-129	

Pictograms

	Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)		KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems		Suspended weighing: Load support with hook on the underside of the balance
	Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required				Battery operation: Ready for battery operation. The battery type is specified for each device
	Easy Touch: Suitable for the connection, data transmission and control through PC, tablet or smartphone.		GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection		Rechargeable battery pack: Rechargeable set
	Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.		GLP/ISO log: With weight, date and time. Only with KERN printers		Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
	Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard		Piece counting: Reference quantities selectable. Display can be switched from piece to weight		Mains adapter: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
	Data interface RS-232: To connect the balance to a printer, PC or network		Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out		Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
	RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible		Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display		Weighing principle: Strain gauges: Electrical resistor on an elastic deforming body
	USB data interface: To connect the balance to a printer, PC or other peripherals		Totalising level A: The weights of similar items can be added together and the total can be printed out		Weighing principle: Tuning fork: A resonating body is electromagnetically excited, causing it to oscillate
	Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals		Percentage determination: Determining the deviation in % from the target value (100 %)		Weighing principle: Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings
	WiFi data interface: To transfer data from the balance to a printer, PC or other peripherals		Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details		Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
	Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.		Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model		Verification possible: The time required for verification is specified in the pictogram
	Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements		Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value		Factory calibration (ISO): The time required for Factory calibration is shown in days in the pictogram
	Interface for second balance: For direct connection of a second balance		Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram		Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
	Network interface: For connecting the scale to an Ethernet network				Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer:

ICS Schneider Messtechnik GmbH
Briesestraße 59
D-16562 Hohen Neuendorf / OT Bergfelde

Tel.: 03303 / 50 40 66
Fax: 03303 / 50 40 68

info@ics-schneider.de
www.ics-schneider.de