

## Gas density indicator Model GDI-100

### Applications

- Medium and high-voltage equipment
- Gas density monitoring of closed SF<sub>6</sub> gas tanks

### Special features

- Case and wetted parts from stainless steel
- On-site display of the pressure standardised to 20 °C [68 °F]
- Temperature-compensated and hermetically sealed, therefore no influence of temperature fluctuations, differences in level and atmospheric pressure fluctuations
- Compensation possible for gas mixtures
- Traceability by serial number



Gas density indicator model GDI-100

### Description

Gas density is a crucial operating parameter for high-voltage switchgear. If the required gas density is not present, safe operation of the plant cannot be guaranteed.

With WIKA gas density measuring instruments, changes of gas volumes can be determined reliably (e.g. leakages). Even under extreme environmental conditions.

#### Numerous fields of application

The WIKA gas density indicator is hermetically sealed and temperature-compensated. Measured value fluctuations and misinterpretations caused by changes in either ambient temperature or atmospheric pressure are therefore prevented.

Via the on-site display, the pressure based on 20 °C [68 °F] can be read directly on the instrument.

## Gas density indicator

### Nominal size

100

### Calibration pressure $P_E$

To customer specification

### Accuracy specifications

- $\pm 1$  % at ambient temperature 20 °C [68 °F]
- $\pm 2.5$  % at ambient temperature -20 ... +60 °C [-4 ... +68 °F]

### Scale range

Vacuum and overpressure range with measuring span of 1.6 ... 25 bar (with an ambient temperature of 20 °C [68 °F] and gaseous phase)

### Permissible ambient temperature

Operation: -20 ... +60 °C [-4 ... +140 °F], gaseous phase

Storage: -50 ... +60 °C [-58 ... +140 °F]

### Process connection

G ½ B per EN 837, lower mount

Stainless steel, spanner flats 22 mm

Other connections and connection locations on request.

### Pressure element

Stainless steel, welded

Gas-tight: leak rate  $\leq 1 \cdot 10^{-8}$  mbar · l / s

Test method: helium mass spectrometry

### Movement

Stainless steel

Bimetal link (temperature compensation)

### Dial

Aluminium

The scale range is subdivided into red, yellow and green ranges

### Pointer

Aluminium, black

### Case

#### Selectable versions

Option 1	Stainless steel, with gas filling
Option 2	Stainless steel, with filling liquid

Gas-tight: leak rate  $\leq 1 \cdot 10^{-5}$  mbar · l / s

### Window

#### Selectable versions

Option 1	Laminated safety glass
Option 2	Clear non-splintering plastic

### Ring

Bayonet ring, stainless steel, secured by means of 3 welding spots

### Permissible humidity

$\leq 90$  % r. h. (non-condensing)

### Ingress protection

IP65 per EN 60529 / IEC 529

### Weight

With gas filling: approx. 0.5 kg

With filling liquid: approx. 0.7 kg

Dimensions in mm

